



RECTANGULAR HAY FEEDERS RECTANGULAR PALISADE FEEDER PŁPC - 1



TECHNICAL DATA:

- body length 200 cm;
- body width 200 cm; - overall height - 274 cm;
- feed fence openable on sides,, enabling loading of feed and cleaning the feeder;
- palisades height 70 cm;
- three-point handle for transport with a tractor (three-point linkage) of
- a feeder not filled with feed;
- removable roof made of aluzinc sheet.

RECTANGULAR PALISADE FEEDER PŁPC - 2



1W10-08-27Rectangular palisade feeder PŁPC-1 HDG2W10-08-29Rectangular palisade feeder PŁPC-2 HDGHDG- anti-corrosion protection - hot-dip galvanized.

TECHNICAL DATA:

- body length 200 cm;
- body width 300 cm;
- overall height 274 cm;
- feed fence openable on sides,, enabling loading of feed and cleaning the feeder;
- palisades height 70 cm;
- three-point handle for transport with a tractor (three-point linkage) of
- a feeder not filled with feed;
- removable roof made of aluzinc sheet.



pcs

pcs





RECTANGULAR DIAGONAL FEEDER PLSC - 1



RECTANGULAR DIAGONAL FEEDER PLSC - 2

TECHNICAL DATA:

- body length 200 cm;
- body width 200 cm;
- overall height 274 cm;
- feed fence openable on sides,, enabling loading of feed and cleaning the feeder;
- feed barriers height- 100 cm;
- three-point handle for transport with a tractor (three-point linkage) of
- a feeder not filled with feed;
- removable roof made of aluzinc sheet.

TECHNICAL DATA:

- body length 200 cm;
- body width 300 cm;
- overall height 274 cm;
- feed fence openable on sides,, enabling loading of feed and cleaning the feeder;
- feed barriers height- 100 cm;
- three-point handle for transport with
- a tractor (three-point linkage) of
- a feeder not filled with feed;
- removable roof made of aluzinc sheet.




 3
 W10-08-75
 Rectangular diagonal feeder PŁSC-1

 4
 W10-08-78
 Rectangular diagonal feeder PŁSC-2

 HDG
 - anti-corrosion protection - hot-dip galvanized.

pcs pcs









RECTANGULAR FEEDER WITH HEADLOCK PŁZC - 1



TECHNICAL DATA:

- body length 200 cm;
- body width 300 cm;
- overall height 274 cm;
- feed fence openable on sides, enabling loading of feed and cleaning the feeder;
- feed barriers height 100 cm;
- three-point handle for transport with a tractor (three-point linkage) of a feeder not filled with feed;
- removable roof made of aluzinc sheet.

RECTANGULAR FEEDER WITH HEADLOCK PŁZC - 2



5W10-08-21Rectangular feeder with headlock PŁZC-1 HDG pcs6W10-08-24Rectangular feeder with headlock PŁZC-2 HDG pcsHDG- anti-corrosion protection - hot-dip galvanized.

TECHNICAL DATA:

- body length 200 cm;
- body width 300 cm;
- overall height 274 cm;
- feed fence openable on sides, enabling loading of feed and cleaning the feeder;
- feed barriers height 100 cm;
- three-point handle for transport with a tractor (three-point linkage) of a feeder not filled with feed;
- removable roof made of aluzinc sheet.








DOUBLE SIDED HAY FEEDERS PŁW PŁW - 2D



- length 260 cm;
- width 78 cm;
- overall height 204 cm, feeder height 120 cm;
- roof made of aluzinc sheet.





- length - 260 cm;

- width 76 cm;
- height 120 cm.
 - 1 **W10-08-41**
 - 2 W10-08-44
 - 3 W10-08-35
 - 4 **W10-08-38**
- Double Sided Hay feeders PŁW 2D HDG Double Sided Hay feeders PŁW - 2PD HDG Double Sided Hay feeders PŁW - 2 HDG
- Double Sided Hay feeders PŁW 2P HDG

CALF CREEP FEEDER PŁC - 1




HDG - anti-corrosion protection - hot-dip galvanized.

PŁW - 2PD



- length 260 cm;
- width 78 cm;
- overall height 204 cm, feeder height 120 cm;
- roof made of aluzinc sheet, stainless steel drinker.

PŁW - 2P



- length 260 cm;
- width 76 cm;
- height 120 cm;
- stainless steel drinker.
- pcs pcs pcs pcs

TECHNICAL DATA:

- feeder box width 200 cm;
- fence length 100 cm;
- fence width 200cm;
- fence width ~ 200 cm;
- overall height 150 cm;
- feeder box capacity 620 l;
- two entrances with adjustable width;
- smooth regulation of dry feed feeding;
- roof with disassembly option;
- three-point linkage for hitching with a tractor.
- openable roof to add feed.

www.rolstal.com







HAY FEEDERS



ROUND DIAGONAL FEEDER PŁSO-1

TECHNICAL DATA:

- number of feed places - 20;

- diameter 170 cm;
- overal height 90 cm;
- consists of two arch elements;
- spacing between bars 20 cm.

ROUND PALISADE FEEDER PŁP-1


TECHNICAL DATA:

- number of feed places 8;
- diameter 145 cm;
- overal height 120 cm;
- palisade height 65 cm;
- consists of two arch elements;
- three-point linkage for hitching with a tractor.



TECHNICAL DATA:

- number of feed places 24;
- diameter 170 cm;
- overal height 90 cm;
- consists of two arch elements;
- spacing between bars 19 cm.







TECHNICAL DATA:

- number of feed places 12;
- diameter 230 cm;
- height 120 cm;
- palisade height- 65 cm;
- consists of three arch element;
- three-point linkage for hitching with a tractor.











DIAGONAL PALISADE FEEDER PLS-1

TECHNICAL DATA:

- number of feed places 14;
- diameter 145 cm;
- height 147 cm;
- spacing between bars 24 cm;
- consists of two arch elements;
- three-point linkage for hitching with a tractor.

DIAGONAL PALISADE FEEDER PŁS-2

TECHNICAL DATA:

- number of feed places 18;
- diameter 230 cm;
- height 138 cm;
- spacing between bars 25 cm;
- consists of three arch elements;
- three-point linkage for hitching with a tractor.



- W10-08-52 5
- 6 W10-08-03
- 7 W10-08-06
- W10-08-09 8
- Diagonal palisade feeder PŁS-2 HDG Diagonal palisade feeder PLS-3 HDG

HDG - anti-corrosion protection - hot-dip galvanized.



pcs

pcs

pcs

pcs

Round palisade feeder PŁP-3 HDG

Diagonal palisade feeder PŁS-1 HDG

ROUND PALISADE FEEDER PŁP-3

TECHNICAL DATA:

- number of feed places -16;
- height 120 cm;
- width 362 cm;
- diameter 200 cm;
- palisade height- 65 cm;
- consists of two arch elements and two
- straigth elements.





DIAGONAL PALISADE FEEDER PŁS-3

TECHNICAL DATA:

- number of feed places 16;
- diameter 230 cm;
- height 144 cm;
- spacing between bars- 31cm;
- consists of three arch elements;
- three-point linkage for hitching with a tractor.

www.rolstal.com