




HAY FEEDERS



ROUND DIAGONAL FEEDER PŁSO-1

TECHNICAL DATA:

- number of feed places - 20;

- diameter 170 cm;
- overal height 90 cm;
- consists of two arch elements;
- spacing between bars 20 cm.

ROUND PALISADE FEEDER PŁP-1


TECHNICAL DATA:

- number of feed places 8;
- diameter 145 cm;
- overal height 120 cm;
- palisade height 65 cm;
- consists of two arch elements;
- three-point linkage for hitching with a tractor.



TECHNICAL DATA:

- number of feed places 24;
- diameter 170 cm;
- overal height 90 cm;
- consists of two arch elements;
- spacing between bars 19 cm.







TECHNICAL DATA:

- number of feed places 12;
- diameter 230 cm;
- height 120 cm;
- palisade height- 65 cm;
- consists of three arch element;
- three-point linkage for hitching with a tractor.











DIAGONAL PALISADE FEEDER PLS-1

TECHNICAL DATA:

- number of feed places 14;
- diameter 145 cm;
- height 147 cm;
- spacing between bars 24 cm;
- consists of two arch elements;
- three-point linkage for hitching with a tractor.

DIAGONAL PALISADE FEEDER PŁS-2

TECHNICAL DATA:

- number of feed places 18;
- diameter 230 cm;
- height 138 cm;
- spacing between bars 25 cm;
- consists of three arch elements;
- three-point linkage for hitching with a tractor.



- W10-08-52 5
- 6 W10-08-03
- 7 W10-08-06
- W10-08-09 8
- Diagonal palisade feeder PŁS-2 HDG Diagonal palisade feeder PLS-3 HDG

HDG - anti-corrosion protection - hot-dip galvanized.



pcs

pcs

pcs

pcs

Round palisade feeder PŁP-3 HDG

Diagonal palisade feeder PŁS-1 HDG

ROUND PALISADE FEEDER PŁP-3

TECHNICAL DATA:

- number of feed places -16;
- height 120 cm;
- width 362 cm;
- diameter 200 cm;
- palisade height- 65 cm;
- consists of two arch elements and two
- straigth elements.





DIAGONAL PALISADE FEEDER PŁS-3

TECHNICAL DATA:

- number of feed places 16;
- diameter 230 cm;
- height 144 cm;
- spacing between bars- 31cm;
- consists of three arch elements;
- three-point linkage for hitching with a tractor.

www.rolstal.com